

ETS-422TW/WS - PA Speaker Column



Weatherproof PA column speakers,
with a top-quality sound.

- Weatherproof and hose-proof, extruded aluminium cabinet
- 100 V line technique
- 2-way version (with additional integrated tweeter for a clearly improved sound)
- Integrated crossover network
- Aluminium front grille
- Supplied with a robust tiltable and movable aluminium wall bracket
- Connection via cable with 4 power taps

Technical data:

| | |
|--------------------------------|----------------------|
| Outdoors | : 1 |
| weatherproof | : 1 |
| 100 V | : 1 |
| Active/passive | : passive |
| Transmission technology | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : - |
| Power rating (RMS) | : 20/10/5/2.5 W |
| Impedance | : - |
| Frequency range | : 130-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : - |
| Full range speaker | : - |
| Bass speaker | : - |
| Midrange speaker | : - |
| Tweeter | : - |
| Number of speakers | : 4+1 |
| Speaker size | : - |
| SPL | : 92 dB/W/m |
| Max. rated SPL | : - |
| Radiation angle/beam angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : aluminium |
| Colour | : white |
| Mounting device | : wall bracket |
| Protected against ball rebound | : - |
| Protection class | : IP66 |
| Admiss. ambient temp. | : -20 °C to +50 °C |
| Power supply | : - |
| Dimensions | : 124 x 610 x 108 mm |

| | |
|--------------------------------|------------------------|
| Width | : 124 mm |
| Height | : 610 mm |
| Depth | : 108 mm |
| Weight | : 4 kg |
| Inputs | : - |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : - |
| Accessories | : - |
| Packing dimensions (W x H x L) | : 0.165 x 0.2 x 0.72 m |
| Gross weight | : 4.84 kg |
| Net weight | : 4.17 kg |