

## ETS-442TW/WS - PA Speaker Column



Weatherproof PA column speakers,  
with a top-quality sound.

- Weatherproof and hose-proof, extruded aluminium cabinet
- 100 V line technique
- 2-way version (with additional integrated tweeter for a clearly improved sound)
- Integrated crossover network
- Aluminium front grille
- Supplied with a robust tiltable and movable aluminium wall bracket
- Connection via cable with 4 power taps

## Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 40/20/10/5 W
Impedance	: -
Frequency range	: 110-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 8+1
Speaker size	: -
SPL	: 93 dB/W/m
Max. rated SPL	: -
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: aluminium
Colour	: white
Mounting device	: wall bracket
Protected against ball rebound	: -
Protection class	: IP66
Admiss. ambient temp.	: -20 °C to +50 °C
Power supply	: -
Dimensions	: 124 x 1,016 x 108 mm



Width	: 124 mm
Height	: 1,016 mm
Depth	: 108 mm
Weight	: 6.9 kg
Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.165 x 0.195 x 1.12 m
Gross weight	: 7.89 kg
Net weight	: 6.96 kg