

## EDL-206 - PA Loudspeaker



### Vejrbestandige indbygningshøjttalere

- 100 V line-teknologi
- Full range højttaler med dual membran, perfekte lydegenskaber
- Stænkæt, udført i et stykke hvidt plastik, polypropylenmembran i høj kvalitet med gummikant
- Til inden- og udendørs anvendelse
- Monteringsskruer i rustfrit stål medfølger

## Technical data:

Impedance (Z)	: -
Transmission technology	: 100 V
Frequency range	: 85-18,000 Hz
Resonant frequency (fs)	: -
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 20/15/10/5/2.5 W
Peak music power output (MAX)	: -
SPL	: 90 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: -
Voice coil former	: -
Linear excursion (X <sub>MAX</sub> )	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: -
Mounting cutout	: $\varnothing$ 132 mm
Mounting depth	: 110 mm
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\varnothing$ 180 mm x 130 mm
Outside diameter	: $\varnothing$ 180 mm

Width	: Å~ 180 mm
Height	: -
Depth	: 130 mm
Colour	: white
Protective class	: IP44
Admiss. ambient temp.	: -30 °C to +40 °C
Weight	: 900 g
Packing unit	: 1
Type of speaker	: 180
Packing dimensions (W x H x L)	: 0.19 x 0.155 x 0.185 m
Gross weight	: 1.048 kg
Net weight	: 0.9 kg
weatherproof	: 1
100 V	: 1