



DT-75/8 - HiFi Dome Tweeter



DT-75/8



Hi-fi dome tweeter, 25 W, 8 Ohm

- Soft dome
- High-quality reproduction
- Ferrofluid

Technical data:

| | |
|---|-----------------------------|
| Impedance (Z) | : 8 Ohm |
| Transmission technology | : - |
| Frequency range | : fx-20,000 Hz |
| Resonant frequency (fs) | : 2,000 Hz |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : 3,000 Hz |
| Power rating (RMS) | : 25 W |
| Peak music power output (MAX) | : 50 W |
| SPL | : 90 dB/W/m |
| Max. rated SPL | : - |
| Max. voltage | : - |
| Radiation angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Suspension compl. (Cms) | : - |
| Moving mass (Mms) | : - |
| Mech. Q factor (Qms) | : - |
| Electr. Q factor (Qes) | : - |
| Total Q factor (Qts) | : - |
| Equivalent volume (Vas) | : - |
| DC resistance (Re) | : - |
| Force factor (BxL) | : - |
| Voice coil induct. (Le) | : - |
| Voice coil diameter | : \hat{A} 25 mm |
| Voice coil former | : - |
| Linear excursion (X _{MAX}) | : - |
| Eff. cone area (Sd) | : - |
| Magnet weight | : - |
| Magnet diameter | : \hat{A} 60 mm |
| Mounting cutout | : 62 x 70 mm |
| Mounting depth | : 28 mm |
| Mounting hole diameter | : - |
| Hole spacing X-axis | : - |
| Hole spacing Y-axis | : - |
| Dimensions | : 93 x 69 x 28 \hat{A} mm |
| Outside diameter | : - |



| | |
|--------------------------------|--------------------------|
| Width | : 93 mm |
| Height | : 69 mm |
| Depth | : 28 mm |
| Colour | : black |
| Protective class | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Weight | : 0.335 kg |
| Packing unit | : 1 |
| Type of speaker | : - |
| Packing dimensions (W x H x L) | : 0.08 x 0.045 x 0.105 m |
| Gross weight | : 0.365 kg |
| Net weight | : 0.335 kg |
| Low-impedance | : 1 |