

RL-1ENABDS - Wall Speaker



PA A/B sound projector for wall mounting,
with EN 54-24 certification for voice evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 13 cm full range speaker with dual voice coil
- 2 x 100 V transformer with power taps on the cable 6/3/1.5 W
- Connection via 2 x 4-core cable (length: 1.5 m)
- Metal housing with front protective grille
- Supplied with pan/tilt bracket and mounting accessories

Technical data:

100 V	: 1
EN 54 certification	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: -
Power rating (RMS)	: 2 x 6/3/1.5 W
Impedance	: -
Frequency range	: 80-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: -
Full range speaker	: 13 cm, dual voice coil
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: -
Speaker size	: 13 cm
SPL	: 93 dB/W/m
Max. rated SPL	: 101 dB
Radiation angle/beam angle	: 130°
Radiation angle, horizontal	: 130°
Radiation angle, vertical	: 130°
Features	: -
Housing material	: aluminium
Colour	: white
Mounting device	: bracket
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: -10 °C to +55 °C
Power supply	: -
Dimensions	: 144 mm x 210 mm
Width	: 144 mm



Height	: -
Depth	: 210 mm
Weight	: 2.3 kg
Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.185 x 0.285 x 0.185 m
Gross weight	: 2.51 kg
Net weight	: 2.32 kg