

ESP-215/WS - PA Wall Speaker



Vejrbestandigt PA højtalersystem, i hvidt plastikkabinet med frontgitter i aluminium

- 100 V teknologi
- 5 tapsætninger, 8 Ohm eller 100 V
- 2-vejs system
- Monteringsbeslag i rustfrit stål

Technical data:

Outdoors	: 1
weatherproof	: 1
100 V	: 1
Low-impedance	: 1
Active/passive	: passive
Transmission technology	: 100 V
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 60 W
Power rating (RMS)	: 15/10/5/2.5/1.5 W (100 V) 30 W (8 Ohm)
Impedance	: 8 Ohm
Frequency range	: 100-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way
Full range speaker	: -
Bass speaker	: -
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 2
Speaker size	: -
SPL	: 87 dB/W/m
Max. rated SPL	: -
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: white
Mounting device	: mounting bracket
Protected against ball rebound	: -
Protection class	: IP65
Admiss. ambient temp.	: -30 °C to +50 °C
Power supply	: -



Dimensions	: 98 x 195 x 105 mm
Width	: 98 mm
Height	: 195 mm
Depth	: 105 mm
Weight	: 0.85 kg
Inputs	: spring-load. speaker term.
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.14 x 0.21 x 0.14 m
Gross weight	: 1.074 kg
Net weight	: 0.934 kg