

## WALL-06T/SW - PA Speaker Cabinet



Pair of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in black
- 4 power taps as well as switchable to 8 Ohm operation
- 16 cm (6") bass-midrange speaker and 25 mm (1") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

## Technical data:

|                                |                                     |
|--------------------------------|-------------------------------------|
| Outdoors                       | : 1                                 |
| 100 V                          | : 1                                 |
| Low-impedance                  | : 1                                 |
| Active/passive                 | : passive                           |
| Transmission technology        | : 100 V                             |
| Total output power             | : -                                 |
| Power rating (RMS)             | : -                                 |
| Total power rating             | : 100 W                             |
| Power rating (RMS)             | : 32/16/8/4 W (100 V) 50 W (8 Ohm)  |
| Impedance                      | : 8 Ohm                             |
| Frequency range                | : 70-20,000 Hz                      |
| THD                            | : -                                 |
| S/N ratio                      | : -                                 |
| Input signal                   | : -                                 |
| System                         | : 2-way                             |
| Full range speaker             | : -                                 |
| Bass speaker                   | : 16 cm (6") bass-midrange speaker  |
| Midrange speaker               | : -                                 |
| Tweeter                        | : 25 mm (1") dome tweeter           |
| Number of speakers             | : 2                                 |
| Speaker size                   | : 6"                                |
| SPL                            | : 90 dB/W/m                         |
| Max. rated SPL                 | : 106 dB                            |
| Radiation angle/beam angle     | : -                                 |
| Radiation angle, horizontal    | : -                                 |
| Radiation angle, vertical      | : -                                 |
| Features                       | : -                                 |
| Housing material               | : plastic                           |
| Colour                         | : black                             |
| Mounting device                | : mounting bracket                  |
| Protected against ball rebound | : -                                 |
| Protection class               | : IP65                              |
| Admiss. ambient temp.          | : 0-40 °C                           |
| Power supply                   | : -                                 |
| Dimensions                     | : 196 x 303 x 250 mm (with bracket) |

|                                |                              |
|--------------------------------|------------------------------|
| Width                          | : 196 mm                     |
| Height                         | : 303 mm                     |
| Depth                          | : 250 mm                     |
| Weight                         | : 3.5 kg                     |
| Inputs                         | : spring-load. speaker term. |
| Outputs                        | : -                          |
| Replacement voice coil         | : -                          |
| Other features                 | : for pivoting and tilting   |
| Accessories                    | : -                          |
| Packing dimensions (W x H x L) | : 0.235 x 0.33 x 0.505 m     |
| Gross weight                   | : 7.63 kg                    |
| Net weight                     | : 6.97 kg                    |