

TXS-812SET - Wireless Microphone



Trådløst 2-kanals mikrofonsystem

- 2 trådløse mikrofoner, 1 modtager, 1 strømforsyning
- To-kanals UHF version (non-diversity) med mixerfunktion
- Volumen- og squelch kontrol for hver kanal
- Hver kanal har LED-indikator for RF signal og lydsignal

Licensfrit i EU.

Technical data:

Hand-held microphone	: 1
General information	:
Description	: wireless microphone system
Carrier frequency range	: 863.80 MHz , 864.20 MHz
Audio frequency range	: 40-15,000 Hz
Channels	: 2
THD	: < 0.5%
Dynamic range	: ? 90 dB
Latency	:
RF S/N ratio	: ? 80 dB
Operating time	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: -
Total weight	: -
Connections	: -
Specifications transmitter	:
Transmitting power	: < 10 mW
Operating range	: approx. 30 m
Power supply transmitter	: 2 x 1.5 V batt. AA size (not supplied)
Width transmitter	: 52 mm
Height transmitter	: 52 mm
Depth transmitter	: 260 mm
Weight transmitter	: 240 g
Connections transmitter	: -
Specifications receiver	:
Audio signal receiver	: 0-200 mV/10 kOhm (jack) 0-400 mV/10 kOhm (XLR, bal.)
Power supply receiver	: via encl. plug-in power supply
Width receiver	: 210 mm
Height receiver	: 46 mm
Depth receiver	: 190 mm
Weight receiver	: 560 g
Connections receiver	: 2 x XLR, bal. 1 x 6.3 mm jack, unbal.