

# PA-1414MX - 10-Channel PA Pre-Amplifier



## 10-kanals PA-forforstærker

- 5 XLR indgange, mic/line
- 4 indgange, XLR mic/phono line
- 2 XLR master udgange
- 1 record udgang (master1, master2)
- Indgange med volumenkontrol og udgangsvælger (master1, master1+2, master2)
- Begge master udgange har 2-vejs tonekontrol
- Gongtaste med prioritet, mulighed for fjernbetjening, 2-toners eller 4-toners gong, sirene
- 1 push-to-talk tilslutning, RJ45, med prioritet (passer til PA-4000PTT)
- Low cut filter til hver mikrofonindgang
- Prioritet for kanaler 2-3
- Phantom strømforsyning til elektret mikrofoner kan tilsluttes XLR-indgangene
- Tilsluttes stikkontakt eller 24 V nødstrømforsyning

## Technical data:

|                                          |                                                                          |
|------------------------------------------|--------------------------------------------------------------------------|
| Peak output power                        | : -                                                                      |
| Power rating                             | : -                                                                      |
| Power rating at 2 Ohm                    | : -                                                                      |
| Power rating at 4 Ohm                    | : -                                                                      |
| Power rating at 8 Ohm                    | : -                                                                      |
| Power rating at 16 Ohm                   | : -                                                                      |
| Power rating at 100 V                    | : -                                                                      |
| Power rating with 4 Ohm                  | : -                                                                      |
| bridged operation                        |                                                                          |
| Power rating with 8 Ohm                  | : -                                                                      |
| bridged operation                        |                                                                          |
| Output impedance                         | : -                                                                      |
| Channels                                 | : 10                                                                     |
| Zones                                    | : -                                                                      |
| Inputs                                   | : 2.5 mV, bal. (mic), 250 mV, bal. (line XLR), 250 mV, unbal. (line RCA) |
| Attenuation factor                       | :                                                                        |
| Frequency range                          | : 20-20,000 Hz (-0.5 dB)                                                 |
| Crossover network                        | : -                                                                      |
| Crossover frequency                      | : -                                                                      |
| Integrated limiter                       | : -                                                                      |
| Equalizer bass                           | : $\pm 10$ dB/100 Hz                                                     |
| Equalizer midrange                       | : -                                                                      |
| Equalizer treble                         | : $\pm 10$ dB/10 kHz                                                     |
| S/N ratio                                | : ? 60 dB (mic), ? 75 dB (line)                                          |
| Crosstalk attenuation                    | : -                                                                      |
| THD                                      | : < 0.05%                                                                |
| Phantom power                            | : -                                                                      |
| Mains voltage                            | : $\sim$ 230 V                                                           |
| Mains frequency                          | : 50 Hz                                                                  |
| Power consumption, operation             | : 15 VA                                                                  |
| Power consumption, standby               | : -                                                                      |
| Standby current                          | : -                                                                      |
| Operating voltage (possible alternative) | : DC 24 V                                                                |
| Power supply (possible alternative)      | : DC 0.5 A                                                               |

Admiss. ambient temp.

: 0-40 °C

Width

: 482 mm

Height

: 45 mm



**MONACOR**



|                                |                                                                                                                                            |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Depth                          | : 240 mm                                                                                                                                   |
| Rack units, RU                 | : 1                                                                                                                                        |
| Weight                         | : 2.5 kg                                                                                                                                   |
| Connections                    | : 9 x XLR (mic/line inputs), 4 x RCA L/R (line inputs), 1 x RJ45 (push-to-talk microphone), 2 x XLR (outputs), 1 x RCA L/R (record output) |
| Packing dimensions (W x H x L) | : 0.34 x 0.14 x 0.55 m                                                                                                                     |
| Gross weight                   | : 3.61 kg                                                                                                                                  |
| Net weight                     | : 2.57 kg                                                                                                                                  |