

MX-1IO - 1-Channel Recording Interface



1-channel USB recording interface

- Integrated USB audio interface (will be identified and addressed as an external sound card)
- Full-duplex USB port (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC and for recording mixings onto a PC
- 1 mono input channel with XLR input (mic) and 6.3 mm input (switchable mic/line)
- Selectable 20 dB attenuation and LED level display
- 1 additional stereo input
- 1 x 6.3 mm jack output L/R
- 1 x 3.5 mm stereo jack output
- Adjustable headphone output
- +48 V phantom power, can be activated as required
- Stereo LED level display
- Robust metal housing of compact size

Technical data:

Input channels	: -
Number of mix/mono	: -
No. of stereo	: -
No. of channels	: 1
No. of inputs	: 3
Mic input	: 2.5 mV, 1 x 3-pole XLR
Line input	: 45 mV, 1 x 6.3 mm jack 11 kOhm (line)/460 kOhm (inst.)
CD input	: -
Phono input	: -
Tape (play)	: -
Aux input	: 1.25 V, 1 x 3.5 mm jack
Insert input	: -
Effect return	: -
Master output	: 500 mV, 1 x 6.3 mm jack L/R
Record output	: -
Monitor output	: -
Booth output	: -
Aux output	: 500 mV, 1 x 3.5 mm jack
Insert output	: -
Effect send	: -
Control room	: -
Tape (rec)	: -
Headphones	: 16 Ohm, 1 x 3.5 mm jack
Gooseneck lamp	: -
WiFi	: -
USB	: yes
Bluetooth	: -
Frequency range	: 20-20,000 Hz
THD	: 0.03%
S/N ratio	: -
Crosstalk	: 92 dB
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
equalizer	: -

Talkover	: -
Phantom power	: +48 V
Crossfader	: -
Media player	: -
Amplifier	: -
Power supply	: via USB interface DC 5 V/500 mA
Mains voltage	: -
Mains frequency	: -
Power consumption, operation	: -
Operating voltage (possible alternative)	: DC 5 V
Power supply (possible alternative)	: 500 mA
Admiss. ambient temp.	: 0-40 °C
Width	: 120 mm
Height	: 50 mm
Depth	: 110 mm
Rack units, RU	: -
Weight	: 498 g
Packing dimensions (W x H x L)	: 0.155 x 0.075 x 0.225 m
Gross weight	: 0.701 kg
Net weight	: 0.564 kg