

MOVE-10PMK2 - Passive PA-Box



Professional PA speaker system, 350 W, 8 Ohm

- Compact professional full range bass-reflex system
- Cabinet made of birch plywood
- 25 cm (10", FaitalPro 10PR300) bass speaker
- 25 mm (1", 44 mm voice coil, Celestion CDX1-1747) horn tweeter, can be turned by 90°
- Switchable between passive operation and bi-amp active operation
- Neutral sound tuning
- 'Catch & Carry' carrying handle
- M8 threaded inserts for suspended installation
- 2 x NEUTRIK SPEAKON terminal, in/out
- Stand sleeve, robust front grille
- Ball-proof acc. to DIN 18032, Part 3

Technical data:

Low-impedance	: 1
Active/passive	: passive
Transmission technology	: cable
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 700 W
Power rating (RMS)	: 350 W
Impedance	: 8 Ohm
Frequency range	: 55-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way bass-reflex
Full range speaker	: -
Bass speaker	: 25 cm (10", FatialPro 10PR300)
Midrange speaker	: -
Tweeter	: dyn. 25 mmÂ mid-high range speakerÂ (1", 44 mm voice coil, Celestion CDX1-1747)
Number of speakers	: 2
Speaker size	: 25 cm (10")
SPL	: 96 dB/W/m
Max. rated SPL	: 121 dB
Radiation angle/beam angle	: H: 80°/V: 40°, horn can be turned by 90°
Radiation angle, horizontal	: 80°
Radiation angle, vertical	: 40°
Features	: -
Housing material	: birch plywood
Colour	: black
Mounting device	: -
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 320 x 545 x 350Â mm
Width	: 320 mm
Height	: 545 mm

Depth	: 350 mm
Weight	: 13.9 kg
Inputs	: 1 x NEUTRIK SPEAKON
Outputs	: 1 x NEUTRIK SPEAKON par. out
Replacement voice coil	: -
Other features	: -
Accessories	: MOVE-10/BAG
Packing dimensions (W x H x L)	: 0.32 x 0.545 x 0.35 m
Gross weight	: 14.48 kg
Net weight	: 13.9 kg