

## MOVE-12PMK2 - Passive PA-Box



Professional PA speaker system, 350 W, 8 Ohm

- Compact professional full range bass-reflex system
- Cabinet made of birch plywood
- 30 cm (12", FaitalPro 12PR300) bass speaker
- 25 mm (1", 44 mm voice coil, Celestion CDX1-1747) horn tweeter, can be turned by 90°
- Switchable between passive operation and bi-amp active operation
- Neutral sound tuning
- 'Catch & Carry' carrying handle
- M8 threaded inserts for suspended installation
- 2 x NEUTRIK SPEAKON terminal, in/out
- Stand sleeve, robust front grille
- Ball-proof acc. to DIN 18032, Part 3

## Technical data:

|                                |                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------|
| Low-impedance                  | : 1                                                                             |
| Active/passive                 | : passive                                                                       |
| Transmission technology        | : cable                                                                         |
| Total output power             | : -                                                                             |
| Power rating (RMS)             | : -                                                                             |
| Total power rating             | : 700 W                                                                         |
| Power rating (RMS)             | : 350 W                                                                         |
| Impedance                      | : 8 Ohm                                                                         |
| Frequency range                | : 45-20,000 Hz                                                                  |
| THD                            | : -                                                                             |
| S/N ratio                      | : -                                                                             |
| Input signal                   | : -                                                                             |
| System                         | : 2-way bass-reflex                                                             |
| Full range speaker             | : -                                                                             |
| Bass speaker                   | : 30 cm (12", FaitalPro 12PR300)                                                |
| Midrange speaker               | : -                                                                             |
| Tweeter                        | : dyn. 25 mm mid-high range speaker (1", 44 mm voice coil, Celestion CDX1-1747) |
| Number of speakers             | : 2                                                                             |
| Speaker size                   | : 30 cm (12")                                                                   |
| SPL                            | : 98 dB/W/m                                                                     |
| Max. rated SPL                 | : 124 dB                                                                        |
| Radiation angle/beam angle     | : H: 80°/V: 40°, horn can be turned by 90°                                      |
| Radiation angle, horizontal    | : 80°                                                                           |
| Radiation angle, vertical      | : 40°                                                                           |
| Features                       | : -                                                                             |
| Housing material               | : birch plywood                                                                 |
| Colour                         | : black                                                                         |
| Mounting device                | : M8 threaded inserts                                                           |
| Protected against ball rebound | : -                                                                             |
| Protection class               | : -                                                                             |
| Admiss. ambient temp.          | : 0-40 °C                                                                       |
| Power supply                   | : -                                                                             |
| Dimensions                     | : 350 x 620 x 385 mm                                                            |
| Width                          | : 350 mm                                                                        |
| Height                         | : 620 mm                                                                        |

|                                |                               |
|--------------------------------|-------------------------------|
| Depth                          | : 385 mm                      |
| Weight                         | : 16.4 kg                     |
| Inputs                         | : 1 x NEUTRIK SPEAKON         |
| Outputs                        | : 1 x NEUTRIK SPEAKON par.out |
| Replacement voice coil         | : -                           |
| Other features                 | : -                           |
| Accessories                    | : MOVE-12/BAG                 |
| Packing dimensions (W x H x L) | : 0.4 x 0.65 x 0.37 m         |
| Gross weight                   | : 18.4 kg                     |
| Net weight                     | : 16.39 kg                    |