

STA-700 - Amplifier



Stereo PA-forstærker, 400 W, til generel anvendelse.

- Ventilatorcooling
- 2 x volumenkontrol
- Ground lift
- Højttalerforsinkelse
- Beskyttelseskredsløb med LED-indikator for beskyttelse mod kortslutning, overophedning og overspænding ved udgangene
- 1 LED-indikator for overbelastning (clip) for hver kanal

Technical data:

Peak output power	: 800 W
Power rating	: 400 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 275 W
Power rating at 8 Ohm	: 2 x 200 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 0.85 V/55 kOhm
Attenuation factor	: -
Frequency range	: 10-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: yes
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: 85 dB
Crosstalk attenuation	: ? 43 dB
THD	: < 0.05%
Phantom power	: -
Mains voltage	: 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 1,100 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 96 mm

Depth	: 296 mm
Rack units, RU	: 2
Weight	: 9.4 kg
Connections	: 1 x 6.3 mm jack L/R 1 x RCA L/R 2 x SPEAKER 1 x 6.3 mm jack L/R 2 x pair of screw terminals

Packing dimensions (W x H x L)	: 0.37 x 0.14 x 0.51 m
Gross weight	: 10.28 kg
Net weight	: 9.7 kg