

PSUB-12AKA - Active Subwoofer



De kompakte subwoofere med indbyggede 2.1 aktive moduler med høj ydeevne er egnet til mange formål. De kan udgøre grundlaget for små eller mellemstore kompakte PA-systemer - uden yderligere forstærkere. Mikrofon- og lineindgange kan mixes, og delefrekvensen til subwoofer og de passive satellithøjtalere er justerbar. Det mixede signal kan videresendes til andre systemer via stereo pre out. **Aktiv 2.1 PA subwoofer, 1.200 W**

- Aktiv basrefleks-subwoofersystem i trækabinet
- Indbygget 2.1 aktivt modul
- Effekt: SUB: 500 W, SAT: 2 x 150 W
- 30 cm (12") basenhed med høj effekt og long excursion
- Stereo line- og mic-indgang med gain kontrol
- Justerbar delefrekvens: 80-250 Hz
- 2-vejs tonekontrol til bas og diskant, balance
- Indbygget limiter, clip indikator
- Udførelse i høj kvalitet, indbyggede bærehåndtag
- Frontgitter i metal, flange til montering på stativ, gummifødder

tastenwelt 03/2013

"The small active system (PSUB-12AKA & 2 x PAB-306/SW) can be used for general applications, suitable for entertainers, smaller DJ events or piano bars. Beside its transparent sound, the system impresses by a good workmanship and its features."

+ Good price-performance ratio **tools4music 01/2014**

"Provides a highly appealing sound. The PSUB-12AKA delivers a performance which perfectly matches the

top parts of the MOVE-06. Very compact size yet of a high power capability with a well-tuned sound. In a word: enjoyable!"

Technical data:

active	: 1
Active/passive	: active
Transmission technology	: cable
Total output power	: 1,200 W
Power rating (RMS)	: 500 W (SUB), 2 x 150 W (SAT)
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 30-250 Hz
THD	: -
S/N ratio	: ? 74 dB
Input signal	: 880 mV-7 V (line) 30 mV (mic)
System	: bass-reflex
Full range speaker	: -
Bass speaker	: 30 cm (12") bass speaker
Midrange speaker	: -
Tweeter	: -
Number of speakers	: 1
Speaker size	: 30 cm (12")
SPL	: -
Max. rated SPL	: 123 dB
Radiation angle/beam angle	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: wood
Colour	: black
Mounting device	: stand sleeve
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: ∿ 230 V/50 Hz/1,870 VA
Dimensions	: 460 x 380 x 455 mm
Width	: 460 mm
Height	: 380 mm

Depth	: 455 mm
Weight	: 28 kg
Inputs	: XLR L/R, bal. RCA L/R, unbal. 6.3 mm jack, unbal.
Outputs	: RCA L/R NEUTRIK SPEAKON L/R (sat > 150 Hz)
Replacement voice coil	: -
Other features	: -
Accessories	: -
Packing dimensions (W x H x L)	: 0.58 x 0.5 x 0.58 m
Gross weight	: 32.98 kg
Net weight	: 28.33 kg