

PA-24AD - PA Line Splitter



10-way PA line splitter

- 2 separate inputs
- Stereo operation or mono operation
- Balanced XLR connection for each input and output
- Gain control for each output
- Peak indication for each input
- Mains operation and 24 V emergency power operation

Technical data:

| | |
|-----------------------|--|
| Description | : splitter |
| Frequency range | : 20-20,000Â Hz |
| Control range | : - |
| Control frequencies | : - |
| Input signal | : 0.775 V |
| Input sensitivity | : - |
| Input impedance | : 15 kOhm |
| Output signal | : 0.775 V |
| Output impedance | : 600 Ohm |
| Gain | : - |
| Phantom power | : |
| Compression | : - |
| Gate ratio | : - |
| Crossover frequency | : - |
| High-pass filter | : - |
| Low cut | : - |
| Transmission ratio | : - |
| S/N ratio | : ? 68 dB |
| Channel separation | : - |
| THD | : < 0.05% |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : ∿ 230Â V/50Â Hz/10Â VA DC 24Â V/0.2Â A |
| Dimensions | : 482 x 45 x 235Â mm, 1Â RS |
| Weight | : 2.9 kg |
| Inputs | : 2 x XLR |
| Outputs | : 10 x XLR |
| Other features | : - |