

## FGA-202 - Line Isolator



**Professionel 2-kanals skilletransformer**, til reduktion af signalforstyrrelser og brummelyde.

- 2 indgange, balancerede, kombi XLR/6,3 mm (600 Ohm)
- 2 galvanisk adskilte XLR udgange (600 Ohm) med ground lift
- Frekvensområde: 20-20.000 Hz
- Robust metalkabinet med rigtig god afskærmning, velegnet til scenebrug
- Mål: 125 x 55 x 75 mm
- Vægt: 650 g

**SOUNDCHECK 07/2007** on the FGA-102, FGA-202, LC-31, MC-31 and LSP-102:

"Every musician or sound engineer should have these little helpers in their toolbox. They impress by their unobtrusiveness. Both the robust metal housing and the functionality of these transformers allow to solve many problems on stage or in the studio at a reasonable price." **tools4music 06/2009** on the LSP-102, LC-31, FGA-102, FGA-202, DIB-102

"Recommendable and fit for on-the-road applications. An attractively priced little audio aid, perfect for the 'ever accompanying' tool case."

## Technical data:

Description	: transformer
Frequency range	: 20-20,000 Hz
Control range	: -
Control frequencies	: -
Input signal	: -
Input sensitivity	: -
Input impedance	: 600 Ohm
Output signal	: -
Output impedance	: 600 Ohm
Gain	: -
Phantom power	: -
Compression	: -
Gate ratio	: -
Crossover frequency	: -
High-pass filter	: -
Low cut	: -
Transmission ratio	: -
S/N ratio	: -
Channel separation	: -
THD	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 125 x 55 x 75 mm
Weight	: 650 g
Inputs	: 2 x comb. jack XLR/6.3 mm, bal.
Outputs	: 2 x XLR
Other features	: -