

PA-1200 - PA Amplifier



4-zoners PA-mixerforstærker, mono

- 1 x 120 W
- Lydløs i brug: blæserfrit kølesystem
- Gong, vedvarende tone og hyletone, automatisk mute; 2- eller 4-tonet gong kan også aktiveres via ekstern kontakt
- Bas-, diskant- og mastervolumenkontrol, LED-indikator
- +15 V phantom strømforsyning til kanal 2 og 3
- Forskellige indbygningsmoduler kan købes separat
- 482 mm (19") rack installation med monteringsbeslag PA-1200RM (købes separat)
- Tilsluttes stikkontakt eller benytter 24 V nødstrømforsyning

Technical data:

100 V	: 1
Low-impedance	: 1
Fanless	: 1
Peak output power	: 170 W
Power rating	: 120 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 5
Zones	: 4
Inputs	: 1.5 mV/600 Ohm (mic), 150 mV/47 kOhm (line), 1 mV/47 kOhm (phono)
Attenuation factor	: -
Frequency range	: 80-15,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: ± 10 dB/100 Hz
Equalizer midrange	: -
Equalizer treble	: ± 10 dB/10 kHz
S/N ratio	: ? 60 dB (mic), ? 70 dB (line)
Crosstalk attenuation	: -
THD	: < 1%
Phantom power	: 15 V
Mains voltage	: \sim 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 280 VA
Power consumption, standby	: -
Standby current	: -

Operating voltage (possible
alternative)

: DC 24 V

Power supply (possible
alternative)

: DC 11 A

MONACOR

Admiss. ambient temp.	: 0-40 °C
Width	: 420 mm
Height	: 122 mm
Depth	: 350 mm
Rack units, RU	: -
Weight	: 12.28 kg
Connections	: 1 x 6.3 mm jack (mic input), 3 x XLR, bal. (mic/line inputs), 1 x RCA L + R (line input), 1 x RCA L + R (phono/line input), spring-load. contact (telephone input), spring-load. contact (tuner output), spring-load. contact (chime)
Packing dimensions (W x H x L)	: 0.47 x 0.2 x 0.52 m
Gross weight	: 13.8 kg
Net weight	: 12.28 kg